

HVAC | INDUSTRIAL PLANT | FACILITY | FOOD & BEVERAGE

GOODWAY®

INNOVATIVE & TECHNOLOGY-DRIVEN
MAINTENANCE SOLUTIONS



ALL NEW REDESIGNED
TUBE CLEANERS.
SEE PAGE 6 FOR DETAILS



Proud Recipients of the Presidents'
Excellence in Exporting "E" Award

VIDEO INSPECTION SCOPES AND TUBE LEAK DETECTOR

Flexible Probe Less Than 10,2 mm Diameter



VS-B-10/30

FEATURES

- 307,200 pixels CMOS image sensor
- 63,5 or 89 mm LCD color monitor (depending on model)
- 6 high intensity white LED's
- Flexible image probe
- 53° field of view
- 90° right angle mirror adapter
- Waterproof probe
- Shock resistant optics
- Compatible with SD Card

VS-B-30: Industrial Video Scope, including flexible 9,1 m probe with a 720 x 640 pixels CMOS image sensor, 53° field of view and 6 LED lights, 90° right angle mirror adapter, monitor with mini USB 1.1/2.0 port 4 GB SD card, cables and carrying case.

Note: Also records audio notes.

SPECIFICATIONS

VS-B-10

Power	Built-in rechargeable Li-ion battery
Illumination	6 LED's
Focal Length	20mm - 70mm
Viewing Direction	Standard 0° or 90°
Minimum Radius	50,8 m
Image Transfer	RCA cable
Resolution	Full HQ 720 x 640 pixels
Interface	USB 1.1/2.0
Still Image Recording Format	JPEG
Video Recording Format	MPEG4/AVI
Operating Temperature	-20° C - 60 °C
Dimensions	Probe: 3 m or 8 m long; Screen: 88.9 mm digital LCD display
Weight	Monitor: 0.5 Kg; 9 m Probe: .5 Kg; 3 m Probe: 2 Kg



FEATURES

- Visible pressure gauges
- Rugged construction
- Multiple seal sizes
- Quick Connect fittings
- Compact

SPECIFICATIONS LD-2X2

Tube Size Range	19,1 to 25,4 mm I.D.
Air Requirements	Maximum 6,9 BAR at 25 m ³ /h
Dimensions	230 mm (H) x 265 mm (W) x 70 mm (D)
Weight	0,9 Kg (Per Gun)

LD-2X2 - Find Leaks Fast

If your heat exchanger, chiller or condenser tubes have a leak, you might as well be throwing money out the window. Even small leaks can substantially undermine system efficiency. To make matters worse, leaks are often downright impossible to find for even seasoned HVAC technicians. The LD-2X2 is the professional solution for checking optimal tube condition. It performs under pressure, so you don't have to.

LD-2X2: Tube Leak Detector Kit, including two pneumatic guns and carrying case.

Note: Seals not included. Order Seal Kit below.

SEAL KITS:

LDW-075: Seal Kit with two seals for tubes 19,1 mm O.D., 16 to 18 gauge and two seals for tubes 19,1 mm O.D., 19 to 22 gauge.

LDW-078: Seal Kit with two seals for tubes 22,2 mm O.D., 16 to 18 gauge and two seals for tubes 22,2 mm O.D., 19 to 22 gauge.

LDW-100: Seal Kit with two seals for tubes 25,4 mm O.D., 16 to 18 gauge and two seals for tubes 25,4 mm O.D., 19 to 22 gauge.

OPTIONAL:

LDA-058A: Adapter Assemblies (two) for tubes 15,9 mm O.D., 16 to 18 gauge (one for each gun).

LDA-058B: Adapter Assemblies (two) for tubes 15,9 mm O.D., 19 to 22 gauge (one for each gun).

LD2X2-EXTENSION-24": 609,6 mm Leak Detector Extension Tubes, set of two. Available in 304,8 mm- 1219 mm

